VLAN-brick
VLAN-toolbox series
Splitbox & interface for network management

VLAN-brick is a collaboration between our LIGHTING and POWER divisions, which combines a VLAN-toolbox and an MSB into a single device. Despite being housed in one body, each unit has its own power input: the MSB is powered via the connector of your choice (Harting or Socapex), while the network switch is powered over Ethernet via dual EtherCON for redundancy and reliability. The spltibox acts as a compact power distribution unit, allowing you to keep your devices up and running, while the network switch interface helps you manage your data.

- **Dimensions:** 336 x 277 x 120 mm (WxHxD)
- **Weight:** 6.84 kg
- **Number of etherCON connectors:** 8 pcs on output, 2 pcs on input
- **PoE:** 67W *(on ports 9 and 10 only)*
- **Speed of individual etherCON ports:** 1Gb/s
- **Splitbox input:** see available configurations below
- **Splitbox output**: see available configurations below

Variants

VLAN-brick configurations

- *929120* VLAN-brick-H16.8-TOP IN: Harting 16, 8 channels, OUT: PowerCON TRUE1-TOP
- *9291XX* VLAN-brick-H16.6-TOP IN: Harting 16, 6 channels, OUT: PowerCON TRUE1-TOP
- *9291XX* VLAN-brick-SX19.6-TOP IN: Socapex 19, 6 channels, OUT: PowerCON TRUE1-TOP

SRS Group s.r.o reserves the right to make changes to the equipment described in this manual/datasheet without prior notice. (E&OE). © SRS Group s.r.o

SRS Group s.r.o.
Pri majeri 4, 831 07 Bratislava, Slovakia
phone: +421 232 661 800, email: sales@srs-group.com, www.srs-group.com

SRS Group s.r.o reserves the right to make changes to the equipment described in this manual/datasheet without prior notice. (E&OE). © SRS Group s.r.o

SRS Group s.r.o.
Pri majeri 4, 831 07 Bratislava, Slovakia
phone: +421 232 661 800, email: sales@srs-group.com, www.srs-group.com